

**MACHINE FOR PERFORMING MACHINING OPERATIONS ON A WORK-
PIECE AND METHOD OF CONTROLLING SAME**

BACKGROUND OF THE INVENTION

Field of the Invention

The invention relates to the field of computer controlled and laser guided portable machines for machining parts or work-pieces and, in particular, to a machine that uses a laser position determination system to correct errors in the position of the machining head due to uncontrolled movements of the machine or work-piece.

Description of Related Art

Computer controlled milling machines and the like are old in art. They generally consist of a very rigid rails to which is mounted a movable carriage containing a head for mounting a cutter or other tool. The work-piece to be machined is mounted on a very rigid platform and the head is moved thereover. Such machines are so rigid that the head and tool can be precisely positioned under the control of a computer.

Some machines, by the nature of their design, can not position the head and tool to a precise position and thus require supplemental alignment systems. For example, US Patent No. 5,302,833 "Rotational Orientation Sensor For Laser Alignment Control System" by M. R. Mamar, et al.

US Patent No. 5,044,844 "Machining Apparatus" by A. E. Backhouse discloses a machine wherein the machining head is mounted on a carriage

1 located on the end of a boom. The boom pivots in a horizontal plane about an
2 axis on spaced circular rails. A laser alignment system senses any
3 inaccuracies in the level of the rails and adjusts the machining head
4 accordingly. However, this system assumes that the cutting head is always
5 properly positioned. This is because the boom and carriage are robust
6 assemblies and only subject to rail inaccuracies. A somewhat similar system
7 is disclosed in US Patent No. 5,240,359 "Machining Apparatus" also by A. E.
8 Backhouse.

9
10 US Patent No. 5,768,137 "Laser Aligned Robotic Machining System For
11 Use In Rebuilding Heavy Machinery" by R. J. Polidoro, et al. discloses a
12 positioning system for resurfacing and repairing rails and guideways of large
13 heavy machinery. A monorail assembly incorporating the milling head is
14 assembled parallel to the rail. The straightness of the rail is determined by a
15 laser measurement system. This information is fed to a computer and is used
16 to align the monorail with the rail. The rail can then be machined to bring it
17 back into tolerance. However, this machine requires a complex set up
18 procedure and is only adapted to machine rails. It could not be used to
19 machine molds and the like.

20
21 None of the above machines are capable of being brought to a remote
22 site and used to machine a work-piece that has been previously setup in a
23 fixed position. All of the prior art machines require precise alignment of the
24 work-piece to the machine. In addition, none of the prior art machines
25 automatically monitor the position of the cutting head and insure that it is in the
26 proper position during machining operations; thus compensating for any
27 movement of the machine or work-piece.

28
29 Thus, it is a primary object of the invention to provide a portable
30 machine for performing machining operations.

It is another primary object of the invention to provide a portable machine for performing machining operations on a work-piece that does not require precise positioning of the machine prior to commencement of machining operations.

It is a further object of the invention to provide a portable machine for performing machining operations on a work-piece that automatically compensates for any movement, inadvertent or otherwise, of the machine or work-piece being machined.

SUMMARY OF THE INVENTION

The invention is a machine for performing machining operations on a work-piece. In detail, the invention includes a carriage having a movable robotic arm assembly incorporating a head containing a tool for performing the machining operations on the work-piece. A laser position determination system is included for determining the actual spatial relationship of the carriage and the work-piece and provides a first signal representative thereof. The laser position determination system further determines the spatial relationship of the head to the work-piece during actual machining operations on the work-piece and provides a second signal representative thereof. A computer running computational software provides a third signal to the robotic arm for machining the work-piece based on a predetermined spatial relationship between the carriage and the work-piece. The computer is adapted to receive the first and second signals and the software adjusts the third signal based on the actual spatial relationship between the carriage and the work-piece prior to machining operations and between the head and the work-piece during machining operations.

1 In a first embodiment, it is assumed that the work-piece remains in a
2 fixed position, thus it is only the carriage that can move due to vibrations or the
3 like and the robotic arm subject to error in positioning. Thus it is only
4 necessary to initially determine the spatial relationship between the carriage
5 and work-piece and thereafter only monitor the spatial position of the head
6 during machining operations. Therefore, the laser position determination
7 system includes a single laser transceiver assembly and at least one laser
8 target on the carriage, work-piece and head of the robotic arm assembly. The
9 laser transceiver is first used to determine the spatial relationship of the work-
10 piece, then the carriage and then is placed in a tracking mode to track the
11 head during machining operations.

12
13 In the second embodiment, it is assumed that the work-piece may
14 move. For example, the work-piece could be on a conveyor system that
15 passes by the machine. The work-piece could also be stationary, but subject
16 to movements due to vibrations and the like. Preferably, there are three
17 laser transceivers, one to determine the spatial relationship of the work-piece
18 prior and during machining operations, one to determine the spatial
19 relationship of the carriage prior to machining operations and a third to
20 determine the spatial relationship of the head of the robotic arm assembly
21 during machining operations. In this embodiment, the computer program
22 continuously monitors the spatial relationship of the work-piece during
23 machining operations and adjusts the third signal accordingly.

24
25 The method of increasing the accuracy of a machine for performing
26 machining operations on a work-piece, the machine having a movable head
27 containing a tool for performing the machining operations on the work-piece,
28 the head movable to predetermined positions directed a computer program
29 within a computer, includes the steps of:

Sub
A1

1. Determining the actual spatial relationship between the carriage and work-piece prior to machining operations and providing a first signal representative thereof;
2. Continuously determining the actual spatial relationship between the head and work-piece during the performance of machining operations and providing a second signal indicative of the actual position; and
3. Adjusting predetermined spatial relationship of the head during machining operations based on the first and second signals.

The method of using the second embodiment involves the steps of:

1. Continuously determining the actual spatial relationship between the carriage and work-piece and providing a second signal representative thereof;
2. Continuously determining the actual spatial relationship between the head and work-piece during the performance of machining operations and providing a third signal indicative of the actual position;
3. Continuously determining the actual spatial relationship of the work-piece during machining operations and providing a third signal indicative thereof; and
4. Adjusting the spatial relationship of the head based on the difference between the first, second and third signals.

The first embodiment of the machine can be used to perform machining operations on a stationary work-piece while compensating for inadvertent movement of the carriage or positional errors caused by the robotic arm. In the second embodiment inadvertent movement of the carriage, robotic arm errors, as well as unintentional movement of the work-piece can be compensated for. In fact, this latter embodiment could be used with parts on a movable assembly line, because the work-piece position is continuously monitored.

The novel features which are believed to be characteristic of the invention, both as to its organization and method of operation, together with further objects and advantages thereof, will be better understood from the following description in connection with the accompanying drawings in which the presently preferred embodiments of the invention are illustrated by way of examples. It is to be expressly understood, however, that the drawings are for purposes of illustration and description only and are not intended as a definition of the limits of the invention.

BRIEF DESCRIPTION OF THE DRAWINGS

Figure 1 is a side view of the machine and work-piece to be machined.

Figure 2 is a perspective view of the machine and work-piece to be machined.

Figure 3 is a view similar to Figure 1 illustrating the machine actually performing machining operations on the work-piece.

Figure 4A is a first part of a flow chart of process for controlling the machine.

Figure 4B is a second part of the flow chart illustrated in Figure 4A.

Figure 5 is a top view of a second embodiment of the machine illustrating the machining of a work-piece in a first position along a moving conveyor.

Figure 6 is a view similar to Figure 5 illustrating the machine with the conveyor having moved the work-piece to a second position.

Figure 7 is a portion of Figure 4B illustrating a revised In-Situ Processing Step.

DESCRIPTION OF THE PREFERRED EMBODIMENT

Referring to Figures 1-4, a work-piece or part to be machined, indicated by numeral 10, is shown secured to the floor 12 by a mounting fitting 14. As illustrated, the work-piece 10 is rigid foam; however, the work-piece could be a ceramic or metal. The top surface 16 includes three tooling holes 18 in a spaced relationship thereon. The subject machine, generally designated by numeral 19, includes a laser alignment system 20, which comprises a laser transceiver assembly 22 mounted in proximity to the work-piece 10, and three laser targets 24A, 24B and 24C mounted in the tooling holes 18. A typical laser alignment system is fully discussed in US Patent No. 4,714,339 "Three to Five axis Laser Tracking Systems" by K. C. Lau, et al., herein incorporated by reference; although other laser alignment systems can be used.

In detail, the laser transceiver tracking assembly 22 transmits a laser beam, indicated by numeral 26 to the laser targets 24A-C mounted on the work-piece 10 and is directed back to the tracking assembly. An interferometer interferes the source beam with the beam that has traveled twice between the laser transceiver assembly 22 and targets in order to measure the separation. By measuring the directions of the beams relative to the targets, the targets can be located in spatial coordinates and additionally the orientation of the targets can be determined. The measurements are fed to a laser-tracking computer (not shown), which is able to calculate the spatial coordinates of the tool 10. Systems based on this technology are commercially available. It must be noted that while three laser targets are shown, in some applications a single target may be adequate.

1 The machine 19 further includes a portable carriage 28 having a robotic
 2 arm assembly 30 mounted on top. The carriage 28 includes wheels 32,
 3 stabilizing jacks 34 and a computer 36. As illustrated the robotic arm has a
 4 tool head 38 in which is mounted a cutter 40. Robotic arms are commercially
 5 available from companies such as Fanuc Robotics, Rochester Hills, MI. The
 6 front face 42 of the carriage 28 includes three laser targets 44A, 44B and 44C
 7 in a spaced relationship, although in some applications, a single target can be
 8 used. While the targets 44A-C are shown positioned on the front face 42
 9 other positions are possible such as on the top surface 43. The carriage 28 is
 10 wheeled up to the work-piece 10 and locked in place by the jacks 34.
 11 Preferably, the carriage 28 is positioned in a predetermined optimum position
 12 in relationship to the work-piece 10. This optimum position would be the
 13 position of carriage as originally set in the machining program in the computer
 14 36. However, even if the carriage is set with precise hand measurements,
 15 they will not generally be precise enough, such that compensation for
 16 positional error must be taken into account.

17
 18 Thus the alignment system 20 is used to determine the spatial
 19 relationship of carriage 28 to the work-piece 10 using the targets 24A-C and
 20 44A-C. Again, it should be noted that in some cases a single target 44A might
 21 suffice. The spatial coordinates of the work-piece 10 and carriage 28 are
 22 provided to the computer 36. Since the relationship between the carriage 28
 23 and robotic arm assembly 30 will be known by the computer 36, the
 24 relationship of the robotic arm to the work-piece can be computed. Thus the
 25 computer 36 can calculate the actual offsets to the spatial relationship required
 26 to compensate for the actual position of the carriage 28 to the work-piece 10.

27
 28 As previously stated, the carriage 10, even if locked in place by the
 29 jacks 34, may move and the robotic arm assembly 30 may introduce
 30 inaccuracies, and the work-piece 10 is not necessarily on a rigid platform, as in

the case of a typical milling machine or the like. Therefore, it is possible that such movement, even if extremely small, could cause inaccuracies in the machining operations. Thus a laser target 46 is mounted on the head 38 of the robotic arm assembly 30. The laser transceiver assembly 22 uses the target 46 to locate the actual spatial relationship of the head 38 during actual machining operations. This information is provided to the computer 36, which continuously adjusts the position of the head 38 so that it is in the required spatial relationship to the work-piece 10.

In Figure 4 is a flow chart of the machining process. The flow chart is divided into four sections:

1. Set up 50, wherein the work-piece and carriage positions are determined. The carriage 28 is wheeled into position in proximity to the work-piece 10. Once in position, the jacks 34 are engaged so that all the weight of the carriage 28 is on the jacks. Note, while desirable, the carriage 28 need not be level or in a particular orientation. The laser alignment system 20 is used to determine the position of the work-piece 10 and carriage 28. The data on the coordinates of both the work-piece and carriage are used to update the computer program within the computer 36 for machining the work-piece.
2. Pre-Processing 52, wherein the computer processes the positional information and up-dates the machining program. The position information is stored in the computer 36 and is used to calculate a coordinate transformation matrix that will be applied to adjust the robotic arm assembly 30 to machine the work-piece 10. This allows the tool 40 to be moved to any position necessary to perform the machining operations on the work-piece.
3. In-Situ Processing 54, wherein the work-piece is machined with the laser tracker assembly providing head 38 position information to correct for errors. Prior to machining operations, transceiver assembly 22 will focus

on the target 46 on the head 38 of the robotic arm assembly 30 and go into a live feedback tracking mode. The robotic arm assembly 30 will follow the preprogrammed computer program that has been modified by the incorporation of actual positions of the carriage 28 and work-piece 10. However, the transceiver assembly receives real-time head 38 spatial relationship information. If there is a deviation, the computer program calculates a difference or offset matrix and uses it to "real time" re-position the head 38 to the required position. This process is updated several times a second insuring a smooth machining operation.

4. Post Processing 56, wherein the work-piece is inspected. After the machining operation, the robotic arm assembly 30 is used to inspect the work-piece 10. It will replace the cutter 40 with an inspection target (not shown). The transceiver assembly 22 tracks the inspection targets' position as the now the machined work-piece is probed. In detail, the flow chart is as follows.

Section 1, Set up 50 involves steps of:

Step 60-Set up carriage 28 and alignment system 20 in proximity to the work-piece 10.

Step 62-Determination of positional relationship of work-piece to the robotic arm assembly 30 of the carriage 28 and provides the information to the computer 36.

Section 2, Pre Processing 52 involves the steps:

Step 64-Store positional information in computer 36.

Step 66-Perform coordinate transformation to generate transformation matrix

Step 68-Update machining program using transformation matrix.

Section 3, In-Situ Processing 54 involves the steps of:

Step 70-Transceiver assembly 22 tracks target 46.

Step 72-Machine to preprogrammed path.

Step 73-Measure actual position of head

Step 75-Determine if head 38 at proper position. Computer program determines deviation between actual head position and desired position. If the head 38 is at the proper position, to Step 76.

Step 76-Determine if machining is complete. If complete then to Step 78 of Post Processing 56 Section. If machining is not complete then Step 80.

Step 80-Generate a delta transformation matrix and calculate offsets.

Thereafter return to Step 72

Section 4, Post Processing 56

Step 78-Robotic arm assembly 30 replaces cutter 40 and inserts a spring loaded laser target (not shown)

Step 82-Machine work-piece inspected.

Step 84-Record measured data

Step 86-compare measured data with desired surface contour. If not within tolerance, return to step 80, if within tolerance then job is complete.

A second embodiment of the invention is depicted in Figures 5 and 6. Here work-pieces 90A, 90B and 90C are shown mounted on a conveyor system 92 and have two slots 94A and 94B shown on completed part 90C, partially machined on work-piece 90B and in dotted lines on part 90A. The carriage 28' is identical to carriage 28 except that the laser targets 44A, 44B and 44C are mounted on the top surface 43. The tool 40 mounted in the head 38 of the robotic arm 30 is shown machining the slot 94A in the work-piece 90B. In Figure 6, the work-piece 90B, which has moved further down the conveyor system 92 and the machine has machined the slot 94A and has started to machine slot 94B. A support column 96 extends up from the floor 12, which includes a horizontal arm 98 extending over the conveyor system 92 and carriage 28'. The arm 98 mounts three laser transceiver assemblies

1 100A, for tracking laser targets 44A-44C; 100B for tracking laser targets 24A,
2 24B and 24C mounted on the work-piece 90B; and 100C for tracking laser
3 target 46 mounted on the head 38. The spatial relationships of the work-piece
4 90B and head 38 can be tracked as the conveyor system 92 moves the work-
5 pieces there along. Note that is not necessary to track the carriage 28' during
6 the machining operations because the head 38 is monitored. Therefore, the
7 laser transceiver 100C could be used to initially locate the carriage 28' and
8 thereafter used to monitor head 38 position; thus only two laser transceiver
9 assemblies are really necessary.

10
11 Referring to Figure 7, the process is similar to that disclosed in Figure
12 4B except the In-Situ Processing Section, now indicated by numeral 54',
13 includes a "Step 73A Determination of actual position of work-piece" between
14 "Step 73-Determine if head is in proper position" and "Step 74- Is mill at proper
15 position 74. In Step 73A, the laser transceiver assembly 100B tracks the
16 targets 24A, B and C to determine if the work-piece has moved from its initial
17 position.

18
19 Thus the invention can be used to perform machining operations on a
20 work-piece. In the first embodiment, it can accommodate movement
21 inadvertent movement between the work-piece and carriage. In the second
22 embodiment, the machine can accommodate continuous movement between
23 the carriage and work-piece. Furthermore, while a conveyor system was
24 shown for purposes of illustration, a basically stationary work-piece, subject to
25 small movements, could easily accommodated. Additionally, it should also be
26 noted that while the machining operations discussed were milling, hole drilling
27 or other operations can be performed with the machine.

28
29 While the invention has been described with reference to particular
30 embodiments, it should be understood that the embodiments are merely

1 illustrative, as there are numerous variations and modifications, which may be
2 made by those skilled in the art. Thus, the invention is to be construed as
3 being limited only by the spirit and scope of the appended claims.

4

5 **INDUSTRIAL APPLICABILITY**

6

7 The invention has applicability to the machine tool industry.

8

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196